

Installing your S7 KeySafe™

Before you begin, please remember:

- It may be easier to set or change your key safe code before you install it.
- If possible we recommend you install your key safe out of line of easy sight for passers-by and in a position of good light to make it easier for the user
- You must use the included bolts
- Do not mount your key safe closer than 6" or 15cm to the corner of a masonry surface
- Make sure your key safe is mounted flush with the masonry surface and only installed directly into brick. Never install into mortar and minimize all gaps between back of the vault and the masonry surface
- If you are relocating your key safe you will need to purchase new bolts. These bolts can be purchased online or by calling our customer service team on 01905 770333



Installing your KeySafe

To correctly install your S7 KeySafe you will need the following items: Power drill, hammer & screwdriver, 8mm drill bit suitable for masonry, a 10mm socket set, a pencil and tape.

1. Prior to fitting your KeySafe to the wall you will need to punch out the 4 guide holes in the back of the KeySafe using a hammer and screwdriver. This will enable the bolt thread to pass through.
2. Using the KeySafe as a guide, mark each of the 4 drill holes with pencil on your wall. Ensure that all 4 holes are going into solid brick and not the mortar lines.
3. Using a small amount of tape, mark the required drill depth on your 8mm masonry drill bit. The minimum drill depth is 80mm deep.
4. Ensure all four of the dynabolt nuts are finger tight and tap them into the drilled holes in the wall, taking care not to damage the thread on the bolt.
5. Using a 10mm socket set, tighten the nuts to the dynobolts by 3 turns. This will ensure the dynobolts are secure and the sleeve is tight to the bolt. After you have done this remove the nuts from the dynobolts completely and set aside.
6. Now offer the vault of the KeySafe to the wall over the dynobolts and replace the nuts.
7. Again using your socket set, tighten each of the four nuts to the dynobolts carefully. Take care not to overtighten and check that your KeySafe is flush to the wall.

If you experience difficulties during the installation, please contact The Key Safe Company on 01905 770333 and we will do our best to assist you over the phone.

Questions? Give us a call on 01905 770 333